Parameter

Spacings

Number of Rows

		Lingine		
Machine Weight	15 T		Rated Rotation Speed	2200RPM
Cotton Collection Tank Capacity	28m³ with liftable tank		Idle Speed	850 ~ 1000RPM
		Picking Head	Alternator	28V70A
Dimension	8125x4553x4975		Number of Picking Head	5
Unloading type	Automatic		Drums	5×2 (10)
Power Supply Voltage	24DVC		Bars	5×2×12 (120)
Battery Pack	2X12V165AH		Spindles	5×432 (2160)
Driving control system	Hydraulic variable speed &3 speed mechanical transmission		Picking head speed	1480RPM
Fuel Tank Capacity	400 L		Spindle Speed	4322RPM
Cleaning Liquid Tank	1000 L	Driving speed	Height Control Type	Hydraulic Copying
Hydraulic Oil Tank	220 L		Field Range I	0-6.0KM/H
Grease Filling	External quick plug		Field Range II	0-7.5KM/H

Eingine

Power

Model

Transport Range

Rear Steering Wheel

Front Driving wheel

Reverse

325HP

0-25KM/H

0-4km/h

Rim: W13-24 Tyre 14.9-24

Rim: W18-38 Tyre 20.8-38

Cummins OSL8.9-325

Hydraulic System

Fan rotation speed

Electric System

Features

5

1.High-power turbocharged engine with powerful performance

Danfoss

Danfoss

3950RPM

2.Advanced electronic controlled automatic gearbox, One button control with more accuracy and reliability

76cm (66+10 Or 62+14) and 90cm

3. Fully electronic controlled operation, say goodbye to variable speed line, throttle line etc.

4.Large-capacity cotton tank with double layers to reduce the unloading time, with more working efficiency

5.Picking head, fan, and driving mechanism are all powered by hydraulic motors with more reliability and easier operation

6.Luxurious cabin with large space and large viewing angle, clean and comfortable environment, relieve fatigue

7.The air is blown by the vertical fan, provides stronger wind and faster picking speed, greatly reduced the cotton blockage

8. Unique engine compartment warming waterway design, no longer freezes when picking cotton 9. Newly enhanced integral welded rear axle, increased widened low pressure rear wheel, more stable cotton picking and better work quality